

Universe	Professional
Type	Verticality
Category	Lanyards and energy absorbers
Subcategory	Fall arrest lanyards




ABSORBICA®-Y MGO European Version

ABSORBICA®-Y MGO is a double lanyard with compact energy absorber, designed for progression on a vertical structure or a horizontal lifeline, and for passing intermediate anchors. It functions with users weighing between 50 and 140 kg. It is available in two lengths: 80 or 150 cm versions (without connectors). The 150 cm version has elasticized arms to avoid hindering progression. With two MGO large-opening connectors, it is certified to European and Russian standards.



The ABSORBICA®-Y lanyards with two arms allow for continuous protection by successively detaching and re-attaching the two arms.



In the event of a fall, the tearing of the energy absorber webbing limits the impact force on the user. The lanyards are designed for users who weigh between 50 and 140 kg. The progressive tearing of the webbing reduces the deceleration on lightweight users.



The energy absorber is very compact to avoid hindering the user's movements or interfering with work. A durable fabric pouch helps protect the energy absorber from abrasion and potential contaminants.

Short Description Double lanyard with integrated energy absorber and MGO connectors

Selling Points



- Designed for progression on a vertical structure or horizontal lifeline, and when passing intermediate anchors
- Absorbs energy in the event of a fall:
 - Tearing of the energy absorber webbing limits the impact force on the user
 - Works with users who weigh between 50 and 140 kg (1)
 - Progressive tearing reduces the deceleration on lightweight users
- Minimal bulk:
 - Compact energy absorber facilitates handling
 - FLEX version with 150 cm of elasticized webbing to avoid hindering progression
- Durable fabric pouch with opening system at each end, protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber
- Two options for installation on the harness, depending on use:
 - Frequent connection/disconnection: using either a carabiner held in correct position by the STRING positioning accessory (included with the lanyard), or a MICRO SWIVEL to avoid tangling
 - Semi-permanent connection: using either a RING OPEN gated ring whose circular shape allows optimal positioning, or a SWIVEL OPEN to avoid tangling
- Comes with two large-opening MGO connectors for connection to metal structures
- Available in two lengths: 80 and 150 cm

(1) In compliance with maximum accepted fall distances More information in our technical tips at [Petzl.com](https://www.petzl.com)

Specification

- Material(s): Polyester, nylon, high-modulus polyethylene, aluminum
 - Certification(s): CE EN 355 when used with EN 362, UKCA, EAC connector (maximum certified mass: 100 kg)
-

Specifications by reference

Reference(s)	L012CA00	L014CA01
		
Version	-	FLEX
Length without connectors	80 cm	150 cm
Connector	MGO	MGO
Length with connectors	130 cm	200 cm
Weight	1290 g	1350 g
Made in	RO	RO
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	5	5
EAN	3342540831742	3342540831629

Related product(s) NEWTON European version
 VOLT® European Version
 OK
 Am'D
 RING OPEN
 MICRO SWIVEL